PROFESSIONAL LIGHTING

L025130930

LED GX53 75x24mm 230V 680Lm 10W
3000K 930 30° AC Helder Dimbaar

Huishoudelijk, Disc GX53 Premium





General	
Eprel registration no	2054940
Socket	GX53
Width	75.00 mm
Depth	75.00 mm
Height	24.00 mm
Finish	Clear
Colour	Colourless
Colour housing	White
Body material	Polycarbonat
Lifespan	25000 hours
Switches	30000
Beam angle	30 °
Dimmable	Yes
Degree of protection	IP20
Net weight	0.080 kg
Warranty	2 years

Light	
CRI	92
Kelvin	3000 K
Colour temp nr	930
Stable lumen	820 lm
Lumen 90 cone	680 lm
Lumen 120 cone	750 lm
Luminous intensity	1300 cd

Energy	
Operating voltage	230 V
Volt	220..240 V
Frequency	50..60 Hz
Watt	10 W
Current type	AC
Power factor	0.95
Energy efficiency class	G
Energy consumption	10 W
Lamp efficacy	68.00

LED	
Filament LED	No
LED type	SMD 2835
Dimm type	Trailing and leading edge
Number of leds / sticks	1
Colour consistency SDCM	SDCM3
Dim to warm	No
Adjustable beam angle	No

Ordering details		
L025130930	Quantity pc(s)	EAN
Single package	1	8718739072176
Inner carton	10	18718739072173
Outer carton	200	28718739072170

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal