PROFESSIONAL LIGHTING

## L025365030

LED GX53 74x27mm 230V 650Lm 7W
3000K 830 120° AC Opaal Dimbaar

**Huishoudelijk, Disc GX53 Premium**








| General | |
|---|---|
| Eprel registration no | 1811211 |
| Socket | GX53 |
| Width | 74.00 mm |
| Depth | 74.00 mm |
| Height | 27.00 mm |
| Finish | Opal |
| Colour | White |
| Colour housing | White |
| Body material | Polycarbonat |
| Lifespan | 15000 hours |
| Switches | 50000 |
| Beam angle | 120 ° |
| Dimmable | Yes |
| Degree of protection | IP20 |
| Net weight | 0.038 kg |
| Warranty | 2 years |

| Light | |
|---|---|
| CRI | 80 |
| Kelvin | 3000 K |
| Colour temp nr | 830 |
| Stable lumen | 650 lm |
| Lumen 120 cone | 550 lm |
| Luminous intensity | 580 cd |

| Energy | |
|---|---|
| Operating voltage | 230 V |
| Volt | 220..240 V |
| Frequency | 50..60 Hz |
| Watt | 7 W |
| Current type | AC |
| Power factor | 0.9 |
| Energy efficiency class | F |
| Energy consumption | 7 W |
| Lamp efficacy | 92.86 |

| LED | |
|---|---|
| Filament LED | No |
| LED type | SMD 2835 |
| Dimm type | Trailing and leading edge |
| Number of leds / sticks | 14 |
| Colour consistency SDCM | SDCM5 |
| Dim to warm | No |
| Adjustable beam angle | No |

| Ordering details | | |
|---|---|---|
| L025365030 | Quantity pc(s) | EAN |
| Single package | 1 | 8718739071308 |
| Inner carton | 10 | 18718739071305 |
| Outer carton | 100 | 28718739071302 |

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal