



L142901930

LED E14 Tube T29x118mm 230V 1050Lm
10W 3000K 930 360° AC/DC Opaal
Dimbaar

Huishoudelijk, Tubular Premium



General		Energy															
Eprel registration no	831263	Operating voltage	230 V														
Socket	E14	Volt	220..240 V														
Bulb shape	T29	Frequency	50..60 Hz														
Width	29.00 mm	Watt	10 W														
Depth	29.00 mm	Current type	AC/DC														
Height	118.00 mm	Power factor	0.9														
Finish	Opal	Energy efficiency class	F														
Colour	White	Energy consumption	10 W														
Body material	Polycarbonat	Lamp efficacy	105.00														
Lifespan	25000 hours	LED <table><tr><td>Filament LED</td><td>No</td></tr><tr><td>LED type</td><td>SMD</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>72</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	No	LED type	SMD	Dimm type	Trailing and leading edge	Number of leds / sticks	72	Colour consistency SDCM	SDCM6	Dim to warm	No	Adjustable beam angle	No
Filament LED	No																
LED type	SMD																
Dimm type	Trailing and leading edge																
Number of leds / sticks	72																
Colour consistency SDCM	SDCM6																
Dim to warm	No																
Adjustable beam angle	No																
Switches	50000																
Beam angle	360 °																
Dimmable	Yes																
Degree of protection	IP20																
Net weight	0.058 kg																
Warranty	3 years																
Light		Ordering details <table><tr><td>L142901930</td><td>Quantity pc(s)</td><td>EAN</td></tr><tr><td>Single package</td><td>1</td><td>8718739063846</td></tr><tr><td>Inner carton</td><td>10</td><td>18718739063843</td></tr><tr><td>Outer carton</td><td>100</td><td>28718739063840</td></tr></table>		L142901930	Quantity pc(s)	EAN	Single package	1	8718739063846	Inner carton	10	18718739063843	Outer carton	100	28718739063840		
L142901930	Quantity pc(s)	EAN															
Single package	1	8718739063846															
Inner carton	10	18718739063843															
Outer carton	100	28718739063840															
Kelvin	3000 K																
Colour temp nr	930																
Stable lumen	1050 lm																
Color Rendering Index (CRI)	90																