PROFESSIONAL LIGHTING

L149125001

LED E14 DimToWarm Kaars C37x105mm
230V 250Lm 4W 2000-2700K 920-927
270° AC Opaal Dimbaar

Huishoudelijk, Dim To Warm



General	
Eprel registration no	831316
Socket	E14
Bulb shape	C37
Width	37.00 mm
Depth	37.00 mm
Height	105.00 mm
Finish	Opal
Colour	White
Colour housing	White
Body material	Polycarbonat
Lifespan	25000 hours
Switches	50000
Beam angle	270 °
Dimmable	Yes
Degree of protection	IP20
Net weight	0.053 kg
Warranty	2 years

Energy	
Operating voltage	230 V
Volt	220..240 V
Frequency	50..60 Hz
Watt	4 W
Current type	AC
Power factor	0.75
Energy efficiency class	G
Energy consumption	4 W
Lamp efficacy	62.50

LED	
Filament LED	No
LED type	SMD 3628
Dimm type	Trailing and leading edge
Number of leds / sticks	8
Colour consistency SDCM	SDCM6
Dim to warm	Yes
Adjustable beam angle	No

Light	
CRI	97
Kelvin	2200..2700 K
Colour temp nr	920..927
Stable lumen	250 lm

Ordering details		
L149125001	Quantity pc(s)	EAN
Single package	1	8718739049451
Inner carton	10	18718739049458
Outer carton	100	28718739049455

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal