



PROFESSIONAL
LIGHTING

L226080827

LED Ba22d Filament GLS A60x105mm 230V
806Lm 8W 2700K 827 360° AC Helder
Dimbaar

Decoratief, General Ba22d



General		Energy																			
Epel registration no	767171	Operating voltage	230 V																		
Socket	Ba22d	Volt	220..240 V																		
Bulb shape	A60	Frequency	50..60 Hz																		
Width	60.00 mm	Watt	8 W																		
Depth	60.00 mm	Current type	AC																		
Height	105.00 mm	Power factor	0.75																		
Finish	Clear	Energy efficiency class	F																		
Colour	Colourless	Energy consumption	8 W																		
Body material	Glass	Lamp efficacy	100.75																		
Lifespan	15000 hours	LED <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Ceramic</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>4</td></tr><tr><td>Stick length</td><td>53 mm</td></tr><tr><td>Stick mounting</td><td>Straight</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Ceramic	Dimm type	Trailing and leading edge	Number of leds / sticks	4	Stick length	53 mm	Stick mounting	Straight	Colour consistency SDCM	SDCM6	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Ceramic																				
Dimm type	Trailing and leading edge																				
Number of leds / sticks	4																				
Stick length	53 mm																				
Stick mounting	Straight																				
Colour consistency SDCM	SDCM6																				
Dim to warm	No																				
Adjustable beam angle	No																				
Switches	50000																				
Beam angle	360 °																				
Dimmable	Yes																				
Degree of protection	IP20																				
Net weight	0.032 kg																				
Warranty	2 years																				
Light		Ordering details <table><tr><td>L226080827</td><td>Quantity pc(s)</td><td>EAN</td></tr><tr><td>Single package</td><td>1</td><td>8718739065307</td></tr><tr><td>Inner carton</td><td>10</td><td>18718739065304</td></tr><tr><td>Outer carton</td><td>40</td><td>28718739065301</td></tr></table>		L226080827	Quantity pc(s)	EAN	Single package	1	8718739065307	Inner carton	10	18718739065304	Outer carton	40	28718739065301						
L226080827	Quantity pc(s)			EAN																	
Single package	1			8718739065307																	
Inner carton	10			18718739065304																	
Outer carton	40			28718739065301																	
Kelvin	2700 K																				
Colour temp nr	827																				
Stable lumen	806 lm																				
Color Rendering Index (CRI)	82																				



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

12-10-2026