



## L276099925-1

LED E27 Filament GLS A60x106mm 230V  
430Lm 4W 2500K 825 360° AC Goud Light  
Sensor Niet-Dimbaar

## Specials & Projecten, Light Sensor



| General               |             |
|-----------------------|-------------|
| Eprel registration no | 619774      |
| Socket                | E27         |
| Bulb shape            | A60         |
| Width                 | 60.00 mm    |
| Depth                 | 60.00 mm    |
| Height                | 106.00 mm   |
| Finish                | Clear       |
| Colour                | Gold        |
| Body material         | Glass       |
| Lifespan              | 20000 hours |
| Switches              | 10000       |
| Beam angle            | 360 °       |
| Dimmable              | No          |
| Degree of protection  | IP20        |
| Net weight            | 0.023 kg    |
| Warranty              | 2 years     |

| Energy                  |            |
|-------------------------|------------|
| Operating voltage       | 230 V      |
| Volt                    | 220..240 V |
| Frequency               | 50..60 Hz  |
| Watt                    | 4 W        |
| Current type            | AC         |
| Power factor            | 0.5        |
| Energy efficiency class | F          |
| Energy consumption      | 4 W        |
| Lamp efficacy           | 107.50     |

| LED                     |          |
|-------------------------|----------|
| Filament LED            | Yes      |
| LED type                | Ceramic  |
| Dimm type               | Non-Dim  |
| Number of leds / sticks | 4        |
| Stick mounting          | Straight |
| Colour consistency SDCM | SDCM6    |
| Dim to warm             | No       |
| Adjustable beam angle   | No       |

| Ordering details |                |                |
|------------------|----------------|----------------|
| L276099925-1     | Quantity pc(s) | EAN            |
| Single package   | 1              | 8718739064904  |
| Inner carton     | 10             | 18718739064901 |
| Outer carton     | 100            | 28718739064908 |

| Light                       |        |
|-----------------------------|--------|
| Kelvin                      | 2500 K |
| Colour temp nr              | 825    |
| Stable lumen                | 430 lm |
| Color Rendering Index (CRI) | 80     |

| Remark                                                             |  |
|--------------------------------------------------------------------|--|
| This bulb will light up when the sensor detects light below 30lux. |  |

