



PROFESSIONAL  
LIGHTING

## L279514003

LED E27 Filament Flex DH Globe  
G95x135mm 230V 120Lm 5W 2200K 822  
360° AC Smoke Dimbaar

### Decoratief, Flex Double Helix



| General               |             |
|-----------------------|-------------|
| Eprel registration no | 766113      |
| Socket                | E27         |
| Bulb shape            | G95         |
| Width                 | 95.00 mm    |
| Depth                 | 95.00 mm    |
| Height                | 135.00 mm   |
| Finish                | Clear       |
| Colour                | Smoke       |
| Body material         | Glass       |
| Lifespan              | 15000 hours |
| Switches              | 30000       |
| Beam angle            | 360 °       |
| Dimmable              | Yes         |
| Degree of protection  | IP20        |
| Net weight            | 0.067 kg    |
| Warranty              | 2 years     |

| Light                       |        |
|-----------------------------|--------|
| Kelvin                      | 2200 K |
| Colour temp nr              | 822    |
| Stable lumen                | 120 lm |
| Color Rendering Index (CRI) | 80     |

| Energy                  |            |
|-------------------------|------------|
| Operating voltage       | 230 V      |
| Volt                    | 220..240 V |
| Frequency               | 50..60 Hz  |
| Watt                    | 5 W        |
| Current type            | AC         |
| Power factor            | 0.85       |
| Energy efficiency class | G          |
| Energy consumption      | 5 W        |
| Lamp efficacy           | 24.00      |

| LED                     |                           |
|-------------------------|---------------------------|
| Filament LED            | Yes                       |
| LED type                | Flex                      |
| Dimm type               | Trailing and leading edge |
| Number of leds / sticks | 2                         |
| Stick length            | 130 mm                    |
| Stick mounting          | Spiral Double helix       |
| Colour consistency SDCM | SDCM6                     |
| Dim to warm             | No                        |
| Adjustable beam angle   | No                        |

| Ordering details |                |                |
|------------------|----------------|----------------|
| L279514003       | Quantity pc(s) | EAN            |
| Single package   | 1              | 8718739065260  |
| Inner carton     | 5              | 18718739065267 |
| Outer carton     | 50             | 28718739065264 |



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | [www.spl-lighting.com](http://www.spl-lighting.com) | [info@spl-lighting.com](mailto:info@spl-lighting.com) | Telephone +31 (0)76 - 503 77 17  
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

12-10-2026