



L480102465

LED PLL 2G11 4 pin Glas T44x320mm 230V
1550Lm 12W (PLL24W) 6500K 865 AC
Opaal Niet-Dimbaar

Marine & Industrie, PLL 2G11 4pin



General		Energy	
Epel registration no	2039266	Operating voltage	230 V
Socket	2G11	Volt	220..240 V
Bulb shape	T44	Frequency	50..60 Hz
Width	44.00 mm	Watt	12 W
Depth	23.00 mm	Current type	AC
Height	320.00 mm	Power factor	0.9
Finish	Opal	Energy efficiency class	E
Colour	White	Energy consumption	12 W
Colour housing	White	Lamp efficacy	129.17
Body material	Glass	LED	
Lifespan	30000 hours	Filament LED	No
Switches	15000	LED type	SMD 2835
Beam angle	270 °	Dimm type	Non-Dim
Dimmable	No	Number of leds / sticks	72
Degree of protection	IP20	Colour consistency SDCM	SDCM6
Net weight	0.097 kg	Dim to warm	No
Warranty	2 years	Adjustable beam angle	No
Light		Ordering details	
Kelvin	6500 K	L480102465	Quantity pc(s) EAN
Colour temp nr	865	Single package	1 8718739071469
Stable lumen	1550 lm	Inner carton	10 18718739071466
Color Rendering Index (CRI)	80	Outer carton	100 28718739071463