



L480105565

LED PLL 2G11 4 pin Glas T44x530mm 230V
3300Lm 24W (PLL55W) 6500K 865 AC
Opaal Niet-Dimbaar

Marine & Industrie, PLL 2G11 4pin



General		Energy	
Epel registration no	2088075	Operating voltage	230 V
Socket	2G11	Volt	220..240 V
Bulb shape	T44	Frequency	50..60 Hz
Width	44.00 mm	Watt	24 W
Depth	23.00 mm	Current type	AC
Height	530.00 mm	Power factor	0.9
Finish	Opal	Energy efficiency class	D
Colour	White	Energy consumption	24 W
Colour housing	White	Lamp efficacy	137.50
Body material	Glass	LED	
Lifespan	25000 hours	Filament LED	No
Switches	15000	LED type	SMD 2835
Beam angle	270 °	Dimm type	Non-Dim
Dimmable	No	Number of leds / sticks	120
Degree of protection	IP20	Colour consistency SDCM	SDCM6
Net weight	0.149 kg	Dim to warm	No
Warranty	2 years	Adjustable beam angle	No
Light		Ordering details	
Kelvin	6500 K	L480105565	Quantity pc(s) EAN
Colour temp nr	865	Single package	1 8718739071582
Stable lumen	3300 lm	Inner carton	10 18718739071589
Color Rendering Index (CRI)	80	Outer carton	100 28718739071586