PROFESSIONAL LIGHTING

L480200940

LED PLS G23 2 pin GlasT32x159mm 230V
620Lm 4.5W (PLS9W) 4000K 840 AC+CCG
Opaal Niet-Dimbaar

Marine & Industrie, PLS G23 2pin AC+CCG



General	
Eprel registration no	2039279
Socket	G23
Bulb shape	T32
Width	32.00 mm
Depth	21.00 mm
Height	159.00 mm
Finish	Opal
Colour	White
Colour housing	White
Body material	Glass
Lifespan	30000 hours
Switches	15000
Beam angle	270 °
Dimmable	No
Degree of protection	IP20
Net weight	0.034 kg
Warranty	2 years

Energy	
Operating voltage	230 V
Volt	220..240 V
Frequency	50..60 Hz
Watt	5 W
Current type	AC
Power factor	0.9
Energy efficiency class	E
Energy consumption	5 W
Lamp efficacy	124.00

LED	
Filament LED	No
LED type	SMD 2835
Dimm type	Non-Dim
Number of leds / sticks	36
Colour consistency SDCM	SDCM6
Dim to warm	No
Adjustable beam angle	No

Light	
CRI	80
Kelvin	4000 K
Colour temp nr	840
Stable lumen	620 lm

Ordering details		
L480200940	Quantity pc(s)	EAN
Single package	1	8718739071742
Inner carton	10	18718739071749
Outer carton	100	28718739071746

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal