PROFESSIONAL LIGHTING

L480300765

LED PLS 2G7 4 pin Glas T37x121mm 230V
390Lm 3W (PLS7W) 6500K 865 AC Opaal
Niet-Dimbaar

Marine & Industrie, PLS 2G7 4pin AC





General	
Eprel registration no	2039287
Socket	2G7
Bulb shape	T37
Width	37.00 mm
Depth	21.00 mm
Height	121.00 mm
Finish	Opal
Colour	White
Colour housing	White
Body material	Glass
Lifespan	30000 hours
Switches	15000
Beam angle	270 °
Dimmable	No
Degree of protection	IP20
Net weight	0.029 kg
Warranty	2 years

Energy	
Operating voltage	230 V
Volt	220..240 V
Frequency	50..60 Hz
Watt	3 W
Current type	AC
Power factor	0.9
Energy efficiency class	E
Energy consumption	3 W
Lamp efficacy	130.00

LED	
Filament LED	No
LED type	SMD 2835
Dimm type	Non-Dim
Number of leds / sticks	24
Colour consistency SDCM	SDCM6
Dim to warm	No
Adjustable beam angle	No

Light	
CRI	80
Kelvin	6500 K
Colour temp nr	865
Stable lumen	390 lm

Ordering details		
L480300765	Quantity pc(s)	EAN
Single package	1	8718739073333
Inner carton	10	18718739073330
Outer carton	100	28718739073337

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal