PROFESSIONAL LIGHTING

L480300930

LED PLS 2G7 4 pin Glas T37x146mm 230V
580Lm 4.5W (PLS9W) 3000K 830 AC
Opaal Niet-Dimbaar

Marine & Industrie, PLS 2G7 4pin AC





General	
Eprel registration no	2039288
Socket	2G7
Bulb shape	T37
Width	37.00 mm
Depth	21.00 mm
Height	146.00 mm
Finish	Opal
Colour	White
Colour housing	White
Body material	Glass
Lifespan	30000 hours
Switches	15000
Beam angle	270 °
Dimmable	No
Degree of protection	IP20
Net weight	0.033 kg
Warranty	2 years

Energy	
Operating voltage	230 V
Volt	220..240 V
Frequency	50..60 Hz
Watt	4.5 W
Current type	AC
Power factor	0.9
Energy efficiency class	E
Energy consumption	5 W
Lamp efficacy	128.89

LED	
Filament LED	No
LED type	SMD 2835
Dimm type	Non-Dim
Number of leds / sticks	36
Colour consistency SDCM	SDCM6
Dim to warm	No
Adjustable beam angle	No

Light	
CRI	80
Kelvin	3000 K
Colour temp nr	830
Stable lumen	580 lm

Ordering details		
L480300930	Quantity pc(s)	EAN
Single package	1	8718739071834
Inner carton	10	18718739071831
Outer carton	100	28718739071838

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal