



## L480301140

LED PLS 2G7 4 pin Glas T37x205mm 230V  
730Lm 5W (PLS11W) 4000K 840 AC Opaal  
Niet-Dimbaar

### Marine & Industrie, PLS 2G7 4pin



| General                     |             | Energy                  |                    |
|-----------------------------|-------------|-------------------------|--------------------|
| Epel registration no        | 1869522     | Operating voltage       | 230 V              |
| Socket                      | 2G7         | Volt                    | 220..240 V         |
| Bulb shape                  | T37         | Frequency               | 50..60 Hz          |
| Width                       | 37.00 mm    | Watt                    | 5 W                |
| Depth                       | 21.00 mm    | Current type            | AC                 |
| Height                      | 205.00 mm   | Power factor            | 0.5                |
| Finish                      | Opal        | Energy efficiency class | D                  |
| Colour                      | White       | Energy consumption      | 5 W                |
| Colour housing              | White       | Lamp efficacy           | 146.00             |
| Body material               | Glass       | LED                     |                    |
| Lifespan                    | 25000 hours | Filament LED            | No                 |
| Switches                    | 15000       | LED type                | SMD 2835           |
| Beam angle                  | 270 °       | Dimm type               | Non-Dim            |
| Dimmable                    | No          | Number of leds / sticks | 60                 |
| Degree of protection        | IP20        | Colour consistency SDCM | SDCM6              |
| Net weight                  | 0.043 kg    | Dim to warm             | No                 |
| Warranty                    | 2 years     | Adjustable beam angle   | No                 |
| Light                       |             | Ordering details        |                    |
| Kelvin                      | 4000 K      | L480301140              | Quantity pc(s) EAN |
| Colour temp nr              | 840         | Single package          | 1 8718739071865    |
| Stable lumen                | 730 lm      | Inner carton            | 10 18718739071862  |
| Color Rendering Index (CRI) | 80          | Outer carton            | 100 28718739071869 |