



L480402630

LED PLC G24d 2 pin GlasT34x168mm 230V
1280Lm 9W (PLD26W) 3000K 830
AC+CCG Opaal Niet-Dimbaar

Marine & Industrie, PLC G24d 2pin



General		Energy	
Epel registration no	1869523	Operating voltage	230 V
Socket	G24d	Volt	220..240 V
Bulb shape	T34	Frequency	50..60 Hz
Width	34.00 mm	Watt	9 W
Depth	34.00 mm	Current type	AC
Height	168.00 mm	Power factor	0.5
Finish	Opal	Energy efficiency class	D
Colour	White	Energy consumption	9 W
Colour housing	White	Lamp efficacy	142.22
Body material	Glass	LED	
Lifespan	25000 hours	Filament LED	No
Switches	15000	LED type	SMD 2835
Beam angle	270 °	Dimm type	Non-Dim
Dimmable	No	Number of leds / sticks	72
Degree of protection	IP20	Colour consistency SDCM	SDCM6
Net weight	0.072 kg	Dim to warm	No
Warranty	2 years	Adjustable beam angle	No
Light		Ordering details	
Kelvin	3000 K	L480402630	Quantity pc(s) EAN
Colour temp nr	830	Single package	1 8718739071902
Stable lumen	1280 lm	Inner carton	10 18718739071909
Color Rendering Index (CRI)	80	Outer carton	100 28718739071906