PROFESSIONAL LIGHTING

L480501840

LED PLC G24q 4 pin Glas T34x143mm 230V
880Lm 6W (PLDE18W) 4000K 840 AC
Opaal Niet-Dimbaar

Marine & Industrie, PLC G24q 4pin AC





General	
Eprel registration no	2039298
Socket	G24q
Bulb shape	T34
Width	34.00 mm
Depth	34.00 mm
Height	143.00 mm
Finish	Opal
Colour	White
Colour housing	White
Body material	Glass
Lifespan	30000 hours
Switches	15000
Beam angle	270 °
Dimmable	No
Degree of protection	IP20
Net weight	0.062 kg
Warranty	2 years

Energy	
Operating voltage	230 V
Volt	220..240 V
Frequency	50..60 Hz
Watt	6 W
Current type	AC
Power factor	0.9
Energy efficiency class	D
Energy consumption	6 W
Lamp efficacy	146.67

LED	
Filament LED	No
LED type	SMD 2835
Dimm type	Non-Dim
Number of leds / sticks	48
Colour consistency SDCM	SDCM6
Dim to warm	No
Adjustable beam angle	No

Light	
CRI	80
Kelvin	4000 K
Colour temp nr	840
Stable lumen	880 lm

Ordering details		
L480501840	Quantity pc(s)	EAN
Single package	1	8718739071933
Inner carton	10	18718739071930
Outer carton	100	28718739071937

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal