



L480501865

LED PLC G24q 4 pin Glas T34x143mm 230V
880Lm 6W (PLDE18W) 6500K 865 AC
Opaal Niet-Dimbaar

Marine & Industrie, PLC G24q 4pin



General		Energy	
Epel registration no	2039300	Operating voltage	230 V
Socket	G24q	Volt	220..240 V
Bulb shape	T34	Frequency	50..60 Hz
Width	34.00 mm	Watt	6 W
Depth	34.00 mm	Current type	AC
Height	143.00 mm	Power factor	0.9
Finish	Opal	Energy efficiency class	D
Colour	White	Energy consumption	6 W
Colour housing	White	Lamp efficacy	146.67
Body material	Glass	LED	
Lifespan	25000 hours	Filament LED	No
Switches	15000	LED type	SMD 2835
Beam angle	270 °	Dimm type	Non-Dim
Dimmable	No	Number of leds / sticks	48
Degree of protection	IP20	Colour consistency SDCM	SDCM6
Net weight	0.062 kg	Dim to warm	No
Warranty	2 years	Adjustable beam angle	No
Light		Ordering details	
Kelvin	6500 K	L480501865	Quantity pc(s) EAN
Colour temp nr	865	Single package	1 8718739071940
Stable lumen	880 lm	Inner carton	10 18718739071947
Color Rendering Index (CRI)	80	Outer carton	100 28718739071944