



L480603265

LED PLT GX24q 4 pin Glas T49x140mm
230V 1450Lm 10W (PLTE32W) 6500K 865
AC Opaal Niet-Dimbaar

Marine & Industrie, PLT GX24q 4pin



General		Energy	
Epel registration no	2039305	Operating voltage	230 V
Socket	GX24q	Volt	220..240 V
Bulb shape	T49	Frequency	50..60 Hz
Width	49.00 mm	Watt	10 W
Depth	45.00 mm	Current type	AC
Height	140.00 mm	Power factor	0.9
Finish	Opal	Energy efficiency class	D
Colour	White	Energy consumption	10 W
Colour housing	White	Lamp efficacy	145.00
Body material	Glass	LED	
Lifespan	25000 hours	Filament LED	No
Switches	15000	LED type	SMD 2835
Beam angle	270 °	Dimm type	Non-Dim
Dimmable	No	Number of leds / sticks	72
Degree of protection	IP20	Colour consistency SDCM	SDCM6
Net weight	0.094 kg	Dim to warm	No
Warranty	2 years	Adjustable beam angle	No
Light		Ordering details	
Kelvin	6500 K	L480603265	Quantity pc(s) EAN
Colour temp nr	865	Single package	1 8718739072022
Stable lumen	1450 lm	Inner carton	10 18718739072029
Color Rendering Index (CRI)	80	Outer carton	100 28718739072026