



L480604230

LED PLT GX24q 4 pin Glas T49x165mm
230V 1750Lm 13W (PLTE42W) 3000K 830
AC Opaal Niet-Dimbaar

Marine & Industrie, PLT GX24q 4pin



General		Energy	
Epel registration no	1869528	Operating voltage	230 V
Socket	GX24q	Volt	220..240 V
Bulb shape	T49	Frequency	50..60 Hz
Width	49.00 mm	Watt	13 W
Depth	45.00 mm	Current type	AC
Height	165.00 mm	Power factor	0.5
Finish	Opal	Energy efficiency class	E
Colour	White	Energy consumption	13 W
Colour housing	White	Lamp efficacy	134.62
Body material	Glass	LED	
Lifespan	30000 hours	Filament LED	No
Switches	15000	LED type	SMD 2835
Beam angle	270 °	Dimm type	Non-Dim
Dimmable	No	Number of leds / sticks	108
Degree of protection	IP20	Colour consistency SDCM	SDCM6
Net weight	0.110 kg	Dim to warm	No
Warranty	2 years	Adjustable beam angle	No
Light		Ordering details	
Kelvin	3000 K	L480604230	Quantity pc(s) EAN
Colour temp nr	830	Single package	1 8718739072039
Stable lumen	1750 lm	Inner carton	10 18718739072036
Color Rendering Index (CRI)	80	Outer carton	100 28718739072033