



PROFESSIONAL
LIGHTING

L571210930

LED G53 AR111x67mm 12V 690Lm 12W
3000K 930 10° AC/DC Grijs Dimbaar

Specials & Projecten, Spot G53 AR111
Dimmable Premium



General		Energy	
Epel registration no	831527	Operating voltage	12 V
Socket	G53	Volt	10..14 V
Bulb shape	AR111	Frequency	50..60 Hz
Width	111.00 mm	Watt	12 W
Depth	111.00 mm	Current type	AC/DC
Height	67.00 mm	Power factor	0.9
Finish	Clear	Energy efficiency class	G
Colour	Silver	Energy consumption	12 W
Colour housing	Grey	Lamp efficacy	57.50
Body material	Aluminium	LED	
Lifespan	25000 hours	Filament LED	No
Switches	30000	LED type	COB
Beam angle	10 °	Dimm type	Trailing and leading edge
Dimmable	Yes	Number of leds / sticks	1
Degree of protection	IP20	Colour consistency SDCM	SDCM3
Net weight	0.098 kg	Dim to warm	No
Warranty	3 years	Adjustable beam angle	No

Light		Ordering details		
Kelvin	3000 K	L571210930	Quantity pc(s)	EAN
Colour temp nr	930	Single package	1	8718739063600
Stable lumen	750 lm	Inner carton	10	18718739063607
Lumen 90 cone	690 lm	Outer carton	50	28718739063604
Luminous intensity	8000 cd			
Color Rendering Index (CRI)	92			

Remark

Operating temperature: -20° - + 40° - Storage temperature: -20° - + 70° fully closed fixtures will seriously shorten the life



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionallighting](#) | [schiefersignaal](#)