PROFESSIONAL LIGHTING

## L641770502

LED GU10 MR16 Glas 50x54mm 230V 5W
38° AC Rood Dimbaar

**Specials & Projecten, GU10 Colour**






### General

| | |
|---|---|
| Socket | GU10 |
| Bulb shape | MR16 |
| Width | 50.00 mm |
| Depth | 50.00 mm |
| Height | 54.00 mm |
| Finish | Diffused |
| Colour | Silver |
| Colour housing | Silver |
| Body material | Glass |
| Lifespan | 15000 hours |
| Switches | 50000 |
| Beam angle | 38 ° |
| Dimmable | Yes |
| Degree of protection | IP20 |
| Net weight | 0.055 kg |
| Warranty | 2 years |

### Energy

| | |
|---|---|
| Operating voltage | 230 V |
| Volt | 220..240 V |
| Frequency | 50..60 Hz |
| Watt | 5 W |
| Current type | AC |
| Power factor | 0.9 |
| Energy consumption | 5 W |
| Lamp efficacy | 6.00 |

### LED

| | |
|---|---|
| Filament LED | No |
| LED type | COB |
| Dimm type | Trailing edge |
| Number of leds / sticks | 1 |
| Colour consistency SDCM | SDCM6 |
| Dim to warm | No |
| Adjustable beam angle | No |

### Light

| | |
|---|---|
| Stable lumen | 30 lm |
| Luminous intensity | 28 cd |

### Ordering details

| L641770502 | Quantity pc(s) | EAN |
|---|---|---|
| Single package | 1 | 8718739046214 |
| Inner carton | 10 | 18718739046211 |
| Outer carton | 100 | 28718739046218 |

### Remark

General note: GU10 glass versions need to cool down after 8 hrs burning (switch off for half an hour), because of limited heat dissipation

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal