



## L642670030

LED GU10 MR16 50x55mm 230V 700Lm  
6W 3000K 830 36° AC Dimbaar

**Marine & Industrie, Spot GU10  
Dimmable**



| General              |             | Energy                  |            |
|----------------------|-------------|-------------------------|------------|
| Epel registration no | 2037924     | Operating voltage       | 230 V      |
| Socket               | GU10        | Volt                    | 220..240 V |
| Bulb shape           | MR16        | Frequency               | 50..60 Hz  |
| Width                | 50.00 mm    | Watt                    | 6 W        |
| Depth                | 50.00 mm    | Current type            | AC         |
| Height               | 55.00 mm    | Power factor            | 0.9        |
| Finish               | Clear       | Energy efficiency class | D          |
| Colour               | Colourless  | Energy consumption      | 6 W        |
| Colour housing       | White       | Lamp efficacy           | 116.67     |
| Body material        | PVC         | <b>LED</b>              |            |
| Lifespan             | 25000 hours | Filament LED            | No         |
| Switches             | 30000       | LED type                | SMD 2835   |
| Beam angle           | 36 °        | Dimm type               | Triac      |
| Dimmable             | Yes         | Number of leds / sticks | 14         |
| Degree of protection | IP20        | Colour consistency SDCM | SDCM6      |
| Net weight           | 0.034 kg    | Dim to warm             | No         |
| Warranty             | 2 years     | Adjustable beam angle   | No         |

| Light                       |         | Ordering details |                |                |
|-----------------------------|---------|------------------|----------------|----------------|
| Kelvin                      | 3000 K  | L642670030       | Quantity pc(s) | EAN            |
| Colour temp nr              | 830     | Single package   | 1              | 8718739076006  |
| Stable lumen                | 765 lm  | Inner carton     | 10             | 18718739076003 |
| Lumen 90 cone               | 700 lm  | Outer carton     | 100            | 28718739076000 |
| Luminous intensity          | 1194 cd |                  |                |                |
| Color Rendering Index (CRI) | 80      |                  |                |                |

### Remark

General note: GU10 glass versions need to cool down after 8 hrs burning (switch off for half an hour), because of limited heat dissipation

