PROFESSIONAL LIGHTING

## L642799908

LED GU10 DimToWarm MR16 50x58mm
230V 210Lm 5.5W 2000-2800K 820-828
40° AC with Wit and Nickel front Dimbaar

**Huishoudelijk, Dim To Warm Premium**





| General | |
|---|---|
| Eprel registration no | 831624 |
| Socket | GU10 |
| Bulb shape | MR16 |
| Width | 50.00 mm |
| Depth | 50.00 mm |
| Height | 58.00 mm |
| Finish | Diffused |
| Colour | Colourless |
| Colour housing | White |
| Body material | Aluminium |
| Lifespan | 30000 hours |
| Switches | 50000 |
| Beam angle | 40 ° |
| Dimmable | Yes |
| Degree of protection | IP20 |
| Net weight | 0.070 kg |
| Warranty | 3 years |

| Energy | |
|---|---|
| Operating voltage | 230 V |
| Volt | 180..240 V |
| Frequency | 50..60 Hz |
| Watt | 5.5 W |
| Current type | AC |
| Power factor | 0.65 |
| Energy efficiency class | G |
| Energy consumption | 6 W |
| Lamp efficacy | 38.18 |

| LED | |
|---|---|
| Filament LED | No |
| LED type | COB |
| Dimm type | Trailing and leading edge |
| Number of leds / sticks | 1 |
| Colour consistency SDCM | SDCM6 |
| Dim to warm | Yes |
| Adjustable beam angle | No |

| Light | |
|---|---|
| CRI | 85 |
| Kelvin | 2000..2800 K |
| Colour temp nr | 820..828 |
| Stable lumen | 250 lm |
| Lumen 90 cone | 210 lm |
| Luminous intensity | 420 cd |

**Ordering details**

| L642799908 | Quantity pc(s) | EAN |
|---|---|---|
| Single package | 1 | 8718739048379 |
| Inner carton | 10 | 18718739048376 |
| Outer carton | 200 | 28718739048373 |

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal