PROFESSIONAL LIGHTING

## L643052427

LED GU10 Tube T22x52mm 230V 420Lm
4W 2700K 827 AC Mat Dimbaar

**Huishoudelijk, GU10 Tubular**





### General

| | |
|---|---|
| Eprel registration no | 2022180 |
| Socket | GU10 |
| Bulb shape | T22 |
| Width | 22.00 mm |
| Depth | 22.00 mm |
| Height | 52.00 mm |
| Finish | Frosted |
| Colour | Colourless |
| Colour housing | White |
| Body material | Polycarbonat |
| Lifespan | 25000 hours |
| Switches | 15000 |
| Beam angle | 300 ° |
| Dimmable | Yes |
| Degree of protection | IP20 |
| Net weight | 0.022 kg |
| Warranty | 2 years |

### Energy

| | |
|---|---|
| Operating voltage | 230 V |
| Volt | 220..240 V |
| Frequency | 50..60 Hz |
| Watt | 4 W |
| Current type | AC |
| Power factor | 0.9 |
| Energy efficiency class | F |
| Energy consumption | 4 W |
| Lamp efficacy | 105.00 |

### LED

| | |
|---|---|
| Filament LED | No |
| LED type | SMD 2835 |
| Dimm type | Trailing and leading edge |
| Number of leds / sticks | 44 |
| Colour consistency SDCM | SDCM6 |
| Dim to warm | No |
| Adjustable beam angle | No |

### Light

| | |
|---|---|
| CRI | 80 |
| Kelvin | 2700 K |
| Colour temp nr | 827 |
| Stable lumen | 420 lm |

### Ordering details

| L643052427 | Quantity pc(s) | EAN |
|---|---|---|
| Single package | 1 | 8718739075108 |
| Inner carton | 25 | 18718739075105 |
| Outer carton | 500 | 28718739075102 |

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal