PROFESSIONAL LIGHTING

L647800630-1

LED R7s T20x78mm 230V 470Lm 5W
3000K 830 360° AC Helder Dimbaar

Huishoudelijk, R7s





General	
Eprel registration no	1481966
Socket	R7s
Bulb shape	T20
Width	20.00 mm
Depth	20.00 mm
Height	78.00 mm
Finish	Clear
Colour	Colourless
Body material	Ceramic
Lifespan	15000 hours
Switches	50000
Beam angle	360 °
Dimmable	Yes
Degree of protection	IP20
Net weight	0.035 kg
Warranty	2 years

Light	
CRI	80
Kelvin	3000 K
Colour temp nr	830
Stable lumen	470 lm

Energy	
Operating voltage	230 V
Volt	220..240 V
Frequency	50..60 Hz
Watt	5 W
Current type	AC
Power factor	0.8
Energy efficiency class	F
Energy consumption	5 W
Lamp efficacy	94.00

LED	
Filament LED	No
LED type	SMD 2835
Dimm type	Triac
Number of leds / sticks	60
Colour consistency SDCM	SDCM6
Dim to warm	No
Adjustable beam angle	No

Ordering details		
L647800630-1	Quantity pc(s)	EAN
Single package	1	8718739069558
Inner carton	10	18718739069555
Outer carton	100	28718739069552

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal