PROFESSIONAL LIGHTING

L672303027

LED GX16D PAR56 176x127mm 230V
3500Lm 33W 2700K 827 120° AC Helder
Dimbaar

Specials & Projecten, PAR56





General

Eprel registration no	1421493
Socket	GX16d
Bulb shape	PAR56
Width	176.00 mm
Depth	176.00 mm
Height	127.00 mm
Finish	Clear
Colour	Colourless
Colour housing	Silver
Body material	Glass
Lifespan	25000 hours
Switches	15000
Beam angle	120 °
Dimmable	Yes
Degree of protection	IP20
Net weight	1.206 kg
Warranty	2 years

Energy

Operating voltage	230 V
Volt	220..240 V
Frequency	50..60 Hz
Watt	33 W
Current type	AC
Power factor	0.9
Energy efficiency class	D
Energy consumption	33 W
Lamp efficacy	115.15

LED

Filament LED	No
LED type	SMD
Dimm type	Trailing edge
Number of leds / sticks	48
Colour consistency SDCM	SDCM5
Dim to warm	No
Adjustable beam angle	No

Light

CRI	80
Kelvin	2700 K
Colour temp nr	827
Stable lumen	3800 lm
Lumen 120 cone	3500 lm
Luminous intensity	5000 cd

Ordering details

L672303027	Quantity pc(s)	EAN
Single package	1	8718739068698
Outer carton	4	28718739068692

Remark

Suitable for the Italian Fixture: Flos Toio

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal