



PROFESSIONAL
LIGHTING

LX023810308

LED E27 Filament Globe G80x120mm 230V
330Lm 4W 2500K 925 360° AC Opaal
Dimbaar

Decoratief, Globe G80 Premium



General		Energy																			
Eprel registration no	1850318	Operating voltage	230 V																		
Socket	E27	Volt	220..240 V																		
Bulb shape	G80	Frequency	50..60 Hz																		
Width	80.00 mm	Watt	4 W																		
Depth	80.00 mm	Current type	AC																		
Height	120.00 mm	Power factor	0.88																		
Finish	Opal	Energy efficiency class	G																		
Colour	White	Energy consumption	4 W																		
Body material	Glass	Lamp efficacy	82.50																		
Lifespan	25000 hours	LED <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Ceramic</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>4</td></tr><tr><td>Stick length</td><td>38 mm</td></tr><tr><td>Stick mounting</td><td>BIG Nest</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM5</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Ceramic	Dimm type	Trailing and leading edge	Number of leds / sticks	4	Stick length	38 mm	Stick mounting	BIG Nest	Colour consistency SDCM	SDCM5	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Ceramic																				
Dimm type	Trailing and leading edge																				
Number of leds / sticks	4																				
Stick length	38 mm																				
Stick mounting	BIG Nest																				
Colour consistency SDCM	SDCM5																				
Dim to warm	No																				
Adjustable beam angle	No																				
Switches	50000																				
Beam angle	360 °																				
Dimmable	Yes																				
Degree of protection	IP20																				
Net weight	0.035 kg																				
Warranty	2 years																				
Light																					
Kelvin	2500 K																				
Colour temp nr	925																				
Stable lumen	330 lm																				
Color Rendering Index (CRI)	93																				
		Ordering details																			
		LX023810308	Quantity pc(s) EAN																		
		Single package	1 8718739071339																		
		Inner carton	5 18718739071336																		
		Outer carton	50 28718739071333																		



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)