PROFESSIONAL LIGHTING

LX023811505

LED E14 Filament Kaars Gedraaid
C35x100mm 230V 140Lm 2W 2000K 920
360° AC Goud Dimbaar

Decoratief, Twisted Candle Premium





General	
Eprel registration no	1468300
Socket	E14
Bulb shape	C35
Width	35.00 mm
Depth	35.00 mm
Height	100.00 mm
Finish	Clear
Colour	Gold
Body material	Glass
Lifespan	25000 hours
Switches	50000
Beam angle	360 °
Dimmable	Yes
Degree of protection	IP20
Net weight	0.013 kg
Warranty	2 years

Light	
CRI	95
Kelvin	2000 K
Colour temp nr	920
Stable lumen	140 lm

Energy	
Operating voltage	230 V
Volt	220..240 V
Frequency	50..60 Hz
Watt	2 W
Current type	AC
Power factor	0.8
Energy efficiency class	G
Energy consumption	2 W
Lamp efficacy	70.00

LED	
Filament LED	Yes
LED type	Ceramic
Dimm type	Trailing and leading edge
Number of leds / sticks	2
Stick length	38 mm
Stick mounting	Twisted
Colour consistency SDCM	SDCM6
Dim to warm	No
Adjustable beam angle	No

Ordering details		
LX023811505	Quantity pc(s)	EAN
Single package	1	8718739069060
Inner carton	10	18718739069067
Outer carton	100	28718739069064

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal