



LX023811509

LED E14 Filament Kaars Gedraaid
C35x100mm 230V 120Lm 2W 2200K 922
360° AC Helder Dimbaar

Decoratief, Twisted Candle Premium



General	
Eprel registration no	1441230
Socket	E14
Bulb shape	C35
Width	35.00 mm
Depth	35.00 mm
Height	100.00 mm
Finish	Clear
Colour	Colourless
Body material	Glass
Lifespan	25000 hours
Switches	15000
Beam angle	360 °
Dimmable	Yes
Degree of protection	IP20
Net weight	0.015 kg
Warranty	2 years

Light	
Kelvin	2200 K
Colour temp nr	922
Stable lumen	120 lm
Color Rendering Index (CRI)	93

Energy	
Operating voltage	230 V
Volt	220..240 V
Frequency	50..60 Hz
Watt	2 W
Current type	AC
Power factor	0.85
Energy efficiency class	G
Energy consumption	2 W
Lamp efficacy	60.00

LED	
Filament LED	Yes
LED type	Ceramic
Dimm type	Trailing and leading edge
Number of leds / sticks	2
Stick length	38 mm
Stick mounting	Vertical
Colour consistency SDCM	SDCM6
Dim to warm	No
Adjustable beam angle	No

Ordering details		
LX023811509	Quantity pc(s)	EAN
Single package	1	8718739068919
Inner carton	10	18718739068916
Outer carton	100	28718739068913

