



PROFESSIONAL
LIGHTING

LX023821502

LED E27 Filament Kogel G45x75mm 230V
150Lm 2W 2500K 925 360° AC Helder
Dimbaar

Decoratief, Ball E27 Premium



General		Energy																			
Epel registration no	1763881	Operating voltage	230 V																		
Socket	E27	Volt	220..240 V																		
Bulb shape	G45	Frequency	50..60 Hz																		
Width	45.00 mm	Watt	2 W																		
Depth	45.00 mm	Current type	AC																		
Height	75.00 mm	Power factor	0.85																		
Finish	Clear	Energy efficiency class	G																		
Colour	Colourless	Energy consumption	2 W																		
Body material	Glass	Lamp efficacy	75.00																		
Lifespan	25000 hours	LED <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Ceramic</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>2</td></tr><tr><td>Stick length</td><td>38 mm</td></tr><tr><td>Stick mounting</td><td>Vertical</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Ceramic	Dimm type	Trailing and leading edge	Number of leds / sticks	2	Stick length	38 mm	Stick mounting	Vertical	Colour consistency SDCM	SDCM6	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Ceramic																				
Dimm type	Trailing and leading edge																				
Number of leds / sticks	2																				
Stick length	38 mm																				
Stick mounting	Vertical																				
Colour consistency SDCM	SDCM6																				
Dim to warm	No																				
Adjustable beam angle	No																				
Switches	50000																				
Beam angle	360 °																				
Dimmable	Yes																				
Degree of protection	IP20																				
Net weight	0.010 kg																				
Warranty	2 years																				
Light		Ordering details <table><tr><td>LX023821502</td><td>Quantity pc(s)</td><td>EAN</td></tr><tr><td>Single package</td><td>1</td><td>8718739071018</td></tr><tr><td>Inner carton</td><td>10</td><td>18718739071015</td></tr><tr><td>Outer carton</td><td>100</td><td>28718739071012</td></tr></table>		LX023821502	Quantity pc(s)	EAN	Single package	1	8718739071018	Inner carton	10	18718739071015	Outer carton	100	28718739071012						
LX023821502	Quantity pc(s)			EAN																	
Single package	1			8718739071018																	
Inner carton	10			18718739071015																	
Outer carton	100			28718739071012																	
Kelvin	2500 K																				
Colour temp nr	925																				
Stable lumen	150 lm																				
Color Rendering Index (CRI)	93																				



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)