



PROFESSIONAL
LIGHTING

LX023870602

LED E27 Filament GLS A60x105mm 230V
630Lm 6.5W 2500K 925 360° AC Helder
Dimbaar

Decoratief, General E27 Premium



General		Energy																			
Eprel registration no	1314400	Operating voltage	230 V																		
Socket	E27	Volt	220..240 V																		
Bulb shape	A60	Frequency	50..60 Hz																		
Width	60.00 mm	Watt	6.5 W																		
Depth	60.00 mm	Current type	AC																		
Height	105.00 mm	Power factor	0.85																		
Finish	Clear	Energy efficiency class	F																		
Colour	Colourless	Energy consumption	7 W																		
Body material	Glass	Lamp efficacy	96.92																		
Lifespan	25000 hours	LED <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Ceramic</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>8</td></tr><tr><td>Stick length</td><td>38 mm</td></tr><tr><td>Stick mounting</td><td>Straight</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Ceramic	Dimm type	Trailing and leading edge	Number of leds / sticks	8	Stick length	38 mm	Stick mounting	Straight	Colour consistency SDCM	SDCM6	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Ceramic																				
Dimm type	Trailing and leading edge																				
Number of leds / sticks	8																				
Stick length	38 mm																				
Stick mounting	Straight																				
Colour consistency SDCM	SDCM6																				
Dim to warm	No																				
Adjustable beam angle	No																				
Switches	15000																				
Beam angle	360 °																				
Dimmable	Yes																				
Degree of protection	IP20																				
Net weight	0.033 kg																				
Warranty	2 years																				
Light		Ordering details <table><tr><td>LX023870602</td><td>Quantity pc(s)</td><td>EAN</td></tr><tr><td>Single package</td><td>1</td><td>8718739067745</td></tr><tr><td>Inner carton</td><td>10</td><td>18718739067742</td></tr><tr><td>Outer carton</td><td>100</td><td>28718739067749</td></tr></table>		LX023870602	Quantity pc(s)	EAN	Single package	1	8718739067745	Inner carton	10	18718739067742	Outer carton	100	28718739067749						
LX023870602	Quantity pc(s)			EAN																	
Single package	1			8718739067745																	
Inner carton	10			18718739067742																	
Outer carton	100	28718739067749																			
Kelvin	2500 K																				
Colour temp nr	925																				
Stable lumen	630 lm																				
Color Rendering Index (CRI)	90																				



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)