



PROFESSIONAL
LIGHTING

LX023890302

LED E14 Filament Tube T25x85mm 230V
320Lm 4W 2500K 925 360° AC Helder
Dimbaar

Decoratief, Tubular Fila Premium



General		Energy																			
Epel registration no	1586999	Operating voltage	230 V																		
Socket	E14	Volt	220..240 V																		
Bulb shape	T25	Frequency	50..60 Hz																		
Width	25.00 mm	Watt	4 W																		
Depth	25.00 mm	Current type	AC																		
Height	85.00 mm	Power factor	0.88																		
Finish	Clear	Energy efficiency class	G																		
Colour	Colourless	Energy consumption	4 W																		
Body material	Glass	Lamp efficacy	80.00																		
Lifespan	25000 hours	LED <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Ceramic</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>4</td></tr><tr><td>Stick length</td><td>38 mm</td></tr><tr><td>Stick mounting</td><td>Vertical</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM5</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Ceramic	Dimm type	Trailing and leading edge	Number of leds / sticks	4	Stick length	38 mm	Stick mounting	Vertical	Colour consistency SDCM	SDCM5	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Ceramic																				
Dimm type	Trailing and leading edge																				
Number of leds / sticks	4																				
Stick length	38 mm																				
Stick mounting	Vertical																				
Colour consistency SDCM	SDCM5																				
Dim to warm	No																				
Adjustable beam angle	No																				
Switches	50000																				
Beam angle	360 °																				
Dimmable	Yes																				
Degree of protection	IP20																				
Net weight	0.015 kg																				
Warranty	2 years																				
Light		Ordering details <table><tr><td>LX023890302</td><td>Quantity pc(s)</td><td>EAN</td></tr><tr><td>Single package</td><td>1</td><td>8718739070035</td></tr><tr><td>Inner carton</td><td>10</td><td>18718739070032</td></tr><tr><td>Outer carton</td><td>100</td><td>28718739070039</td></tr></table>		LX023890302	Quantity pc(s)	EAN	Single package	1	8718739070035	Inner carton	10	18718739070032	Outer carton	100	28718739070039						
LX023890302	Quantity pc(s)			EAN																	
Single package	1			8718739070035																	
Inner carton	10			18718739070032																	
Outer carton	100			28718739070039																	
Kelvin	2500 K																				
Colour temp nr	925																				
Stable lumen	320 lm																				
Color Rendering Index (CRI)	92																				



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

12-10-2026