



PROFESSIONAL
LIGHTING

LX023890512

LED E27 Filament GLS Kopspiegel
A60x105mm 230V 500Lm 6.5W 2500K 925
360° AC Zilver Dimbaar

Decoratief, Top Mirror Premium



General		Energy																			
Eprel registration no	2021894	Operating voltage	230 V																		
Socket	E27	Volt	220..240 V																		
Bulb shape	A60	Frequency	50..60 Hz																		
Width	60.00 mm	Watt	6.5 W																		
Depth	60.00 mm	Current type	AC																		
Height	105.00 mm	Power factor	0.85																		
Finish	Clear	Energy efficiency class	G																		
Colour	Silver	Energy consumption	7 W																		
Body material	Glass	Lamp efficacy	76.92																		
Mirroring type	Top	LED <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Ceramic</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>8</td></tr><tr><td>Stick length</td><td>38 mm</td></tr><tr><td>Stick mounting</td><td>Straight</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Ceramic	Dimm type	Trailing and leading edge	Number of leds / sticks	8	Stick length	38 mm	Stick mounting	Straight	Colour consistency SDCM	SDCM6	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Ceramic																				
Dimm type	Trailing and leading edge																				
Number of leds / sticks	8																				
Stick length	38 mm																				
Stick mounting	Straight																				
Colour consistency SDCM	SDCM6																				
Dim to warm	No																				
Adjustable beam angle	No																				
Lifespan	25000 hours																				
Switches	50000																				
Beam angle	360 °																				
Dimmable	Yes																				
Degree of protection	IP20																				
Net weight	0.033 kg																				
Warranty	2 years																				

Light	
Kelvin	2500 K
Colour temp nr	925
Stable lumen	500 lm
Color Rendering Index (CRI)	93

Ordering details		
LX023890512	Quantity pc(s)	EAN
Single package	1	8718739074804
Inner carton	10	18718739074801
Outer carton	100	28718739074808



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

14-10-2026