



PROFESSIONAL  
LIGHTING

## LX023920105

LED E27 Filament XL Flex Mush  
200x180mm 230V 200Lm 4W 2000K 920  
360° AC Goud Dimbaar

Decoratief, Big Flex Mush Premium



| General                     |             | Energy                  |                           |
|-----------------------------|-------------|-------------------------|---------------------------|
| Epel registration no        | 1603974     | Operating voltage       | 230 V                     |
| Socket                      | E27         | Volt                    | 220..240 V                |
| Width                       | 200.00 mm   | Frequency               | 50..60 Hz                 |
| Depth                       | 200.00 mm   | Watt                    | 4 W                       |
| Height                      | 180.00 mm   | Current type            | AC                        |
| Finish                      | Clear       | Power factor            | 0.88                      |
| Colour                      | Gold        | Energy efficiency class | G                         |
| Body material               | Glass       | Energy consumption      | 4 W                       |
| Lifespan                    | 15000 hours | Lamp efficacy           | 50.00                     |
| Switches                    | 50000       | LED                     |                           |
| Beam angle                  | 360 °       | Filament LED            | Yes                       |
| Dimmable                    | Yes         | LED type                | Flex                      |
| Degree of protection        | IP20        | Dimm type               | Trailing and leading edge |
| Net weight                  | 0.277 kg    | Number of leds / sticks | 1                         |
| Warranty                    | 2 years     | Stick length            | 300 mm                    |
| Light                       |             | Stick mounting          | Spiral Special            |
| Kelvin                      | 2000 K      | Colour consistency SDCM | SDCM5                     |
| Colour temp nr              | 920         | Dim to warm             | No                        |
| Stable lumen                | 200 lm      | Adjustable beam angle   | No                        |
| Color Rendering Index (CRI) | 90          | Ordering details        |                           |
|                             |             | LX023920105             | Quantity pc(s)            |
|                             |             | Single package          | 1                         |
|                             |             | Outer carton            | 4                         |
|                             |             | EAN                     |                           |
|                             |             | 8718739070394           |                           |
|                             |             | 28718739070398          |                           |



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | [www.spl-lighting.com](http://www.spl-lighting.com) | [info@spl-lighting.com](mailto:info@spl-lighting.com) | Telephone +31 (0)76 - 503 77 17  
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)