



PROFESSIONAL
LIGHTING

LX023922105

LED E27 Filament Flex DH Tube
T45x110mm 230V 300Lm 5W 2000K 920
360° AC Goud Dimbaar

Decoratief, Flex Double Helix



General		Energy																			
Eprel registration no	1594375	Operating voltage	230 V																		
Socket	E27	Volt	220..240 V																		
Bulb shape	T45	Frequency	50..60 Hz																		
Width	45.00 mm	Watt	5 W																		
Depth	45.00 mm	Current type	AC																		
Height	110.00 mm	Power factor	0.89																		
Finish	Clear	Energy efficiency class	G																		
Colour	Gold	Energy consumption	5 W																		
Body material	Glass	Lamp efficacy	60.00																		
Lifespan	15000 hours	LED <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Flex</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>1</td></tr><tr><td>Stick length</td><td>130 mm</td></tr><tr><td>Stick mounting</td><td>Spiral Double helix</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Flex	Dimm type	Trailing and leading edge	Number of leds / sticks	1	Stick length	130 mm	Stick mounting	Spiral Double helix	Colour consistency SDCM	SDCM6	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Flex																				
Dimm type	Trailing and leading edge																				
Number of leds / sticks	1																				
Stick length	130 mm																				
Stick mounting	Spiral Double helix																				
Colour consistency SDCM	SDCM6																				
Dim to warm	No																				
Adjustable beam angle	No																				
Switches	30000																				
Beam angle	360 °																				
Dimmable	Yes																				
Degree of protection	IP20																				
Net weight	0.030 kg																				
Warranty	2 years																				
Light		Ordering details <table><tr><td>LX023922105</td><td>Quantity pc(s)</td><td>EAN</td></tr><tr><td>Single package</td><td>1</td><td>8718739069572</td></tr><tr><td>Inner carton</td><td>10</td><td>18718739069579</td></tr><tr><td>Outer carton</td><td>100</td><td>28718739069576</td></tr></table>		LX023922105	Quantity pc(s)	EAN	Single package	1	8718739069572	Inner carton	10	18718739069579	Outer carton	100	28718739069576						
LX023922105	Quantity pc(s)			EAN																	
Single package	1			8718739069572																	
Inner carton	10			18718739069579																	
Outer carton	100			28718739069576																	
Kelvin	2000 K																				
Colour temp nr	920																				
Stable lumen	300 lm																				
Color Rendering Index (CRI)	90																				



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)