



PROFESSIONAL
LIGHTING

LX023925303

LED E27 Filament Flex AX Globe
G125x180mm 230V 150Lm 4.5W 2200K 922
360° AC Smoke Dimbaar

Decoratief, Flex Globe Premium



General		Energy																			
Epel registration no	1314398	Operating voltage	230 V																		
Socket	E27	Volt	220..240 V																		
Bulb shape	G125	Frequency	50..60 Hz																		
Width	125.00 mm	Watt	4.5 W																		
Depth	125.00 mm	Current type	AC																		
Height	180.00 mm	Power factor	0.85																		
Finish	Clear	Energy efficiency class	G																		
Colour	Smoke	Energy consumption	5 W																		
Body material	Glass	Lamp efficacy	33.33																		
Lifespan	15000 hours	LED <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Flex</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>1</td></tr><tr><td>Stick length</td><td>300 mm</td></tr><tr><td>Stick mounting</td><td>Spiral Axial</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Flex	Dimm type	Trailing and leading edge	Number of leds / sticks	1	Stick length	300 mm	Stick mounting	Spiral Axial	Colour consistency SDCM	SDCM6	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Flex																				
Dimm type	Trailing and leading edge																				
Number of leds / sticks	1																				
Stick length	300 mm																				
Stick mounting	Spiral Axial																				
Colour consistency SDCM	SDCM6																				
Dim to warm	No																				
Adjustable beam angle	No																				
Switches	15000																				
Beam angle	360 °																				
Dimmable	Yes																				
Degree of protection	IP20																				
Net weight	0.098 kg																				
Warranty	2 years																				
Light		Ordering details																			
Kelvin	2200 K	LX023925303	Quantity pc(s) EAN																		
Colour temp nr	922	Single package	1 8718739067677																		
Stable lumen	150 lm	Outer carton	20 28718739067671																		
Color Rendering Index (CRI)	92																				



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)