



PROFESSIONAL
LIGHTING

LX023960309

LED E27 Filament Flex AX Rustika
ST64x140mm 230V 220Lm 4W 2200K 922
360° AC Helder Dimbaar

Decoratief, Flex Rustika Premium



General		Energy																			
Eprel registration no	1297389	Operating voltage	230 V																		
Socket	E27	Volt	220..240 V																		
Bulb shape	ST64	Frequency	50..60 Hz																		
Width	64.00 mm	Watt	4 W																		
Depth	64.00 mm	Current type	AC																		
Height	140.00 mm	Power factor	0.85																		
Finish	Clear	Energy efficiency class	G																		
Colour	Colourless	Energy consumption	4 W																		
Body material	Glass	Lamp efficacy	55.00																		
Lifespan	15000 hours	LED <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Flex</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>1</td></tr><tr><td>Stick length</td><td>300 mm</td></tr><tr><td>Stick mounting</td><td>Spiral Axial</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Flex	Dimm type	Trailing and leading edge	Number of leds / sticks	1	Stick length	300 mm	Stick mounting	Spiral Axial	Colour consistency SDCM	SDCM6	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Flex																				
Dimm type	Trailing and leading edge																				
Number of leds / sticks	1																				
Stick length	300 mm																				
Stick mounting	Spiral Axial																				
Colour consistency SDCM	SDCM6																				
Dim to warm	No																				
Adjustable beam angle	No																				
Switches	30000																				
Beam angle	360 °																				
Dimmable	Yes																				
Degree of protection	IP20																				
Net weight	0.043 kg																				
Warranty	2 years																				
Light		Ordering details <table><tr><td>LX023960309</td><td>Quantity pc(s)</td><td>EAN</td></tr><tr><td>Single package</td><td>1</td><td>8718739067219</td></tr><tr><td>Inner carton</td><td>10</td><td>18718739067216</td></tr><tr><td>Outer carton</td><td>100</td><td>28718739067213</td></tr></table>		LX023960309	Quantity pc(s)	EAN	Single package	1	8718739067219	Inner carton	10	18718739067216	Outer carton	100	28718739067213						
LX023960309	Quantity pc(s)			EAN																	
Single package	1			8718739067219																	
Inner carton	10			18718739067216																	
Outer carton	100			28718739067213																	
Kelvin	2200 K																				
Colour temp nr	922																				
Stable lumen	220 lm																				
Color Rendering Index (CRI)	93																				



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

