



PROFESSIONAL  
LIGHTING

LX023980309

LED E27 Filament Flex AX Globe  
G95x135mm 230V 270Lm 4.5W 2200K 922  
360° AC Helder Dimbaar

Decoratief, Flex Globe Premium



| General               |             |
|-----------------------|-------------|
| Eprel registration no | 1654744     |
| Socket                | E27         |
| Bulb shape            | G95         |
| Width                 | 95.00 mm    |
| Depth                 | 95.00 mm    |
| Height                | 135.00 mm   |
| Finish                | Clear       |
| Colour                | Colourless  |
| Body material         | Glass       |
| Lifespan              | 15000 hours |
| Switches              | 50000       |
| Beam angle            | 360 °       |
| Dimmable              | Yes         |
| Degree of protection  | IP20        |
| Net weight            | 0.055 kg    |
| Warranty              | 2 years     |

Light

|                             |        |
|-----------------------------|--------|
| Kelvin                      | 2200 K |
| Colour temp nr              | 922    |
| Stable lumen                | 270 lm |
| Color Rendering Index (CRI) | 93     |

| Energy                  |            |
|-------------------------|------------|
| Operating voltage       | 230 V      |
| Volt                    | 220..240 V |
| Frequency               | 50..60 Hz  |
| Watt                    | 4.5 W      |
| Current type            | AC         |
| Power factor            | 0.85       |
| Energy efficiency class | G          |
| Energy consumption      | 5 W        |
| Lamp efficacy           | 60.00      |

LED

|                         |                           |
|-------------------------|---------------------------|
| Filament LED            | Yes                       |
| LED type                | Flex                      |
| Dimm type               | Trailing and leading edge |
| Number of leds / sticks | 1                         |
| Stick length            | 300 mm                    |
| Stick mounting          | Spiral Axial              |
| Colour consistency SDCM | SDCM5                     |
| Dim to warm             | No                        |
| Adjustable beam angle   | No                        |

Ordering details

|                |                |                |
|----------------|----------------|----------------|
| LX023980309    | Quantity pc(s) | EAN            |
| Single package | 1              | 8718739070608  |
| Inner carton   | 5              | 18718739070605 |
| Outer carton   | 50             | 28718739070602 |



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | [www.spl-lighting.com](http://www.spl-lighting.com) | [info@spl-lighting.com](mailto:info@spl-lighting.com) | Telephone +31 (0)76 - 503 77 17  
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

12-10-2026