



PROFESSIONAL
LIGHTING

LX023981205

LED E27 Filament XXL Flex G200x262mm
230V 250Lm 4W 2000K 920 360° AC Goud
Dimbaar

Decoratief, Big Flex



General		Energy																			
Eprel registration no	1424532	Operating voltage	230 V																		
Socket	E27	Volt	220..240 V																		
Bulb shape	G200	Frequency	50..60 Hz																		
Width	200.00 mm	Watt	4 W																		
Depth	200.00 mm	Current type	AC																		
Height	262.00 mm	Power factor	0.8																		
Finish	Clear	Energy efficiency class	G																		
Colour	Gold	Energy consumption	4 W																		
Body material	Glass	Lamp efficacy	62.50																		
Lifespan	15000 hours	LED <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Flex</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>1</td></tr><tr><td>Stick length</td><td>300 mm</td></tr><tr><td>Stick mounting</td><td>Spiral Axial</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Flex	Dimm type	Trailing and leading edge	Number of leds / sticks	1	Stick length	300 mm	Stick mounting	Spiral Axial	Colour consistency SDCM	SDCM6	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Flex																				
Dimm type	Trailing and leading edge																				
Number of leds / sticks	1																				
Stick length	300 mm																				
Stick mounting	Spiral Axial																				
Colour consistency SDCM	SDCM6																				
Dim to warm	No																				
Adjustable beam angle	No																				
Switches	15000																				
Beam angle	360 °																				
Dimmable	Yes																				
Degree of protection	IP20																				
Net weight	0.300 kg																				
Warranty	2 years																				
Light		Ordering details <table><tr><td>LX023981205</td><td>Quantity pc(s)</td><td>EAN</td></tr><tr><td>Single package</td><td>1</td><td>8718739068865</td></tr><tr><td>Outer carton</td><td>4</td><td>28718739068869</td></tr></table>		LX023981205	Quantity pc(s)	EAN	Single package	1	8718739068865	Outer carton	4	28718739068869									
LX023981205	Quantity pc(s)			EAN																	
Single package	1			8718739068865																	
Outer carton	4			28718739068869																	
Kelvin	2000 K																				
Colour temp nr	920																				
Stable lumen	250 lm																				
Color Rendering Index (CRI)	90																				



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)