



PROFESSIONAL  
LIGHTING

LX024030301

LED Ba15d Filament Kogel G45x75mm 230V  
360Lm 4W 2500K 925 360° AC Mat  
Dimbaar

Decoratief, Ball Ba15d Premium



| General                     |                           | Energy                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |            |                |                |          |                |           |                           |                         |    |                |              |                |                |                         |       |             |    |                       |    |
|-----------------------------|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|----------------|----------------|----------|----------------|-----------|---------------------------|-------------------------|----|----------------|--------------|----------------|----------------|-------------------------|-------|-------------|----|-----------------------|----|
| Epel registration no        | 1654742                   | Operating voltage                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 230 V      |                |                |          |                |           |                           |                         |    |                |              |                |                |                         |       |             |    |                       |    |
| Socket                      | Ba15d                     | Volt                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 220..240 V |                |                |          |                |           |                           |                         |    |                |              |                |                |                         |       |             |    |                       |    |
| Bulb shape                  | G45                       | Frequency                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 50..60 Hz  |                |                |          |                |           |                           |                         |    |                |              |                |                |                         |       |             |    |                       |    |
| Width                       | 45.00 mm                  | Watt                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 4 W        |                |                |          |                |           |                           |                         |    |                |              |                |                |                         |       |             |    |                       |    |
| Depth                       | 45.00 mm                  | Current type                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | AC         |                |                |          |                |           |                           |                         |    |                |              |                |                |                         |       |             |    |                       |    |
| Height                      | 75.00 mm                  | Power factor                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 0.8        |                |                |          |                |           |                           |                         |    |                |              |                |                |                         |       |             |    |                       |    |
| Finish                      | Frosted                   | Energy efficiency class                                                                                                                                                                                                                                                                                                                                                                                                                                                         | F          |                |                |          |                |           |                           |                         |    |                |              |                |                |                         |       |             |    |                       |    |
| Colour                      | Colourless                | Energy consumption                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 4 W        |                |                |          |                |           |                           |                         |    |                |              |                |                |                         |       |             |    |                       |    |
| Body material               | Glass                     | Lamp efficacy                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 90.00      |                |                |          |                |           |                           |                         |    |                |              |                |                |                         |       |             |    |                       |    |
| Lifespan                    | 25000 hours               | <div>LED</div> <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Ceramic</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>4</td></tr><tr><td>Stick length</td><td>38 mm</td></tr><tr><td>Stick mounting</td><td>Twisted</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM5</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table> |            | Filament LED   | Yes            | LED type | Ceramic        | Dimm type | Trailing and leading edge | Number of leds / sticks | 4  | Stick length   | 38 mm        | Stick mounting | Twisted        | Colour consistency SDCM | SDCM5 | Dim to warm | No | Adjustable beam angle | No |
| Filament LED                | Yes                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |            |                |                |          |                |           |                           |                         |    |                |              |                |                |                         |       |             |    |                       |    |
| LED type                    | Ceramic                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |            |                |                |          |                |           |                           |                         |    |                |              |                |                |                         |       |             |    |                       |    |
| Dimm type                   | Trailing and leading edge |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |            |                |                |          |                |           |                           |                         |    |                |              |                |                |                         |       |             |    |                       |    |
| Number of leds / sticks     | 4                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |            |                |                |          |                |           |                           |                         |    |                |              |                |                |                         |       |             |    |                       |    |
| Stick length                | 38 mm                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |            |                |                |          |                |           |                           |                         |    |                |              |                |                |                         |       |             |    |                       |    |
| Stick mounting              | Twisted                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |            |                |                |          |                |           |                           |                         |    |                |              |                |                |                         |       |             |    |                       |    |
| Colour consistency SDCM     | SDCM5                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |            |                |                |          |                |           |                           |                         |    |                |              |                |                |                         |       |             |    |                       |    |
| Dim to warm                 | No                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |            |                |                |          |                |           |                           |                         |    |                |              |                |                |                         |       |             |    |                       |    |
| Adjustable beam angle       | No                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |            |                |                |          |                |           |                           |                         |    |                |              |                |                |                         |       |             |    |                       |    |
| Switches                    | 50000                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |            |                |                |          |                |           |                           |                         |    |                |              |                |                |                         |       |             |    |                       |    |
| Beam angle                  | 360 °                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |            |                |                |          |                |           |                           |                         |    |                |              |                |                |                         |       |             |    |                       |    |
| Dimmable                    | Yes                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |            |                |                |          |                |           |                           |                         |    |                |              |                |                |                         |       |             |    |                       |    |
| Degree of protection        | IP20                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |            |                |                |          |                |           |                           |                         |    |                |              |                |                |                         |       |             |    |                       |    |
| Net weight                  | 0.017 kg                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |            |                |                |          |                |           |                           |                         |    |                |              |                |                |                         |       |             |    |                       |    |
| Warranty                    | 2 years                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |            |                |                |          |                |           |                           |                         |    |                |              |                |                |                         |       |             |    |                       |    |
| Light                       |                           | <div>Ordering details</div> <table><tr><td>LX024030301</td><td>Quantity pc(s)</td><td>EAN</td></tr><tr><td>Single package</td><td>1</td><td>8718739068988</td></tr><tr><td>Inner carton</td><td>10</td><td>18718739068985</td></tr><tr><td>Outer carton</td><td>100</td><td>28718739068982</td></tr></table>                                                                                                                                                                    |            | LX024030301    | Quantity pc(s) | EAN      | Single package | 1         | 8718739068988             | Inner carton            | 10 | 18718739068985 | Outer carton | 100            | 28718739068982 |                         |       |             |    |                       |    |
| LX024030301                 | Quantity pc(s)            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |            | EAN            |                |          |                |           |                           |                         |    |                |              |                |                |                         |       |             |    |                       |    |
| Single package              | 1                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |            | 8718739068988  |                |          |                |           |                           |                         |    |                |              |                |                |                         |       |             |    |                       |    |
| Inner carton                | 10                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |            | 18718739068985 |                |          |                |           |                           |                         |    |                |              |                |                |                         |       |             |    |                       |    |
| Outer carton                | 100                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |            | 28718739068982 |                |          |                |           |                           |                         |    |                |              |                |                |                         |       |             |    |                       |    |
| Kelvin                      | 2500 K                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |            |                |                |          |                |           |                           |                         |    |                |              |                |                |                         |       |             |    |                       |    |
| Colour temp nr              | 925                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |            |                |                |          |                |           |                           |                         |    |                |              |                |                |                         |       |             |    |                       |    |
| Stable lumen                | 360 lm                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |            |                |                |          |                |           |                           |                         |    |                |              |                |                |                         |       |             |    |                       |    |
| Color Rendering Index (CRI) | 90                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |            |                |                |          |                |           |                           |                         |    |                |              |                |                |                         |       |             |    |                       |    |



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | [www.spl-lighting.com](http://www.spl-lighting.com) | [info@spl-lighting.com](mailto:info@spl-lighting.com) | Telephone +31 (0)76 - 503 77 17  
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

13-10-2026