

**LX024070501**

LED Ba22d Filament GLS A60x105mm 230V  
500Lm 5.5W 2500K 925 360° AC Mat  
Dimbaar

**Decoratief, General Ba22d Premium**


| General               |             |
|-----------------------|-------------|
| Eprel registration no | 1586952     |
| Socket                | Ba22d       |
| Bulb shape            | A60         |
| Width                 | 60.00 mm    |
| Depth                 | 60.00 mm    |
| Height                | 105.00 mm   |
| Finish                | Frosted     |
| Colour                | Colourless  |
| Body material         | Glass       |
| Lifespan              | 25000 hours |
| Switches              | 50000       |
| Beam angle            | 360 °       |
| Dimmable              | Yes         |
| Degree of protection  | IP20        |
| Net weight            | 0.030 kg    |
| Warranty              | 2 years     |

| Light                       |        |
|-----------------------------|--------|
| Kelvin                      | 2500 K |
| Colour temp nr              | 925    |
| Stable lumen                | 500 lm |
| Color Rendering Index (CRI) | 93     |

| Energy                  |            |
|-------------------------|------------|
| Operating voltage       | 230 V      |
| Volt                    | 220..240 V |
| Frequency               | 50..60 Hz  |
| Watt                    | 5.5 W      |
| Current type            | AC         |
| Power factor            | 0.9        |
| Energy efficiency class | F          |
| Energy consumption      | 6 W        |
| Lamp efficacy           | 90.91      |

| LED                     |                           |
|-------------------------|---------------------------|
| Filament LED            | Yes                       |
| LED type                | Ceramic                   |
| Dimm type               | Trailing and leading edge |
| Number of leds / sticks | 6                         |
| Stick length            | 38 mm                     |
| Stick mounting          | Straight                  |
| Colour consistency SDCM | SDCM5                     |
| Dim to warm             | No                        |
| Adjustable beam angle   | No                        |

| Ordering details |                |                |
|------------------|----------------|----------------|
| LX024070501      | Quantity pc(s) | EAN            |
| Single package   | 1              | 8718739070028  |
| Inner carton     | 10             | 18718739070025 |
| Outer carton     | 100            | 28718739070022 |