PROFESSIONAL LIGHTING

## LX025301509

LED S14d Fila Spiraal T30x300mm 230V 150Lm 2.8W 2200K 922 360° AC Helder Dimbaar

**Huishoudelijk, S14d Filament Premium**





| General | |
|---|---|
| Eprel registration no | 2022488 |
| Socket | S14d |
| Bulb shape | T30 |
| Width | 47.00 mm |
| Depth | 30.00 mm |
| Height | 300.00 mm |
| Finish | Clear |
| Colour | Colourless |
| Body material | Glass |
| Lifespan | 15000 hours |
| Switches | 25000 |
| Beam angle | 360 ° |
| Dimmable | Yes |
| Degree of protection | IP20 |
| Net weight | 0.075 kg |
| Warranty | 2 years |

| Light | |
|---|---|
| CRI | 95 |
| Kelvin | 2200 K |
| Colour temp nr | 922 |
| Stable lumen | 150 lm |

| Energy | |
|---|---|
| Operating voltage | 230 V |
| Volt | 220..240 V |
| Frequency | 50..60 Hz |
| Watt | 2.8 W |
| Current type | AC |
| Power factor | 0.9 |
| Energy efficiency class | G |
| Energy consumption | 3 W |
| Lamp efficacy | 53.57 |

| LED | |
|---|---|
| Filament LED | Yes |
| Dimm type | Trailing and leading edge |
| Number of leds / sticks | 1 |
| Stick length | 360 mm |
| Stick mounting | Spiral Axial |
| Colour consistency SDCM | SDCM5 |
| Dim to warm | No |
| Adjustable beam angle | No |

| Ordering details | | |
|---|---|---|
| LX025301509 | Quantity pc(s) | EAN |
| Single package | 1 | 8718739072602 |
| Outer carton | 50 | 28718739072606 |

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal