

LX032764505

LED E27 Fila Flex DH Rustika ST64 Glas
64x140mm 230V 460Lm 5W 2200K 822
360° AC Goud 3 Step Dimbaar

Decoratief, Flex 3 Step Dimmable



General		Energy																	
Eprel registration no	1558614	Operating voltage	230 V																
Socket	E27	Volt	220..240 V																
Bulb shape	ST64	Frequency	50..60 Hz																
Width	64.00 mm	Watt	5 W																
Depth	64.00 mm	Current type	AC																
Height	140.00 mm	Power factor	0.5																
Finish	Clear	Energy efficiency class	F																
Colour	Gold	Energy consumption	5 W																
Body material	Glass	Lamp efficacy	92.00																
Lifespan	25000 hours	LED <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Flex</td></tr><tr><td>Dimm type</td><td>3-step</td></tr><tr><td>Number of leds / sticks</td><td>2</td></tr><tr><td>Stick mounting</td><td>Spiral Double helix</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM5</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Flex	Dimm type	3-step	Number of leds / sticks	2	Stick mounting	Spiral Double helix	Colour consistency SDCM	SDCM5	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																		
LED type	Flex																		
Dimm type	3-step																		
Number of leds / sticks	2																		
Stick mounting	Spiral Double helix																		
Colour consistency SDCM	SDCM5																		
Dim to warm	No																		
Adjustable beam angle	No																		
Switches	15000																		
Beam angle	360 °																		
Dimmable	Yes																		
Degree of protection	IP20																		
Net weight	0.045 kg																		
Warranty	2 years																		
Light		Ordering details <table><tr><td>LX032764505</td><td>Quantity pc(s)</td><td>EAN</td></tr><tr><td>Single package</td><td>1</td><td>8718739070431</td></tr><tr><td>Inner carton</td><td>10</td><td>18718739070438</td></tr><tr><td>Outer carton</td><td>100</td><td>28718739070435</td></tr></table>		LX032764505	Quantity pc(s)	EAN	Single package	1	8718739070431	Inner carton	10	18718739070438	Outer carton	100	28718739070435				
LX032764505	Quantity pc(s)			EAN															
Single package	1			8718739070431															
Inner carton	10			18718739070438															
Outer carton	100			28718739070435															
Kelvin	2200 K																		
Colour temp nr	822																		
Stable lumen	460 lm																		
Color Rendering Index (CRI)	80																		
Remark																			
Dimming levels: Step 1: 100% brightness; step 2: 50% brightness; step 3: 25% brightness.																			